

Drain Couplings are designed for use in drainage systems, where the resistance to earth loads and shear forces provided by a shear band is not required. They are available to joint drainage pipes up to 225mm diameter.

Due to the use of modern fabrication methods any coupling can be supplied to site within 24 hours.

Uses

- As a joint for plain ended pipe.
- The repair of an existing drain by the insertion of a new length of pipe.
- As an adaptor between pipes of different materials.
- Jointing short or cut lengths of pipe.
- Provision of rocker pipes adjacent to structures.

DRAIN COUPLINGS • 50 - 225mm

REFERENCE NUMBER	SIZE RANGE (mm)	WIDTH (mm)	T (mm)
MDC 100	85 - 100	100	7
MDC 115	100 - 115	120	7
MDC 122	107 - 122	120	7
MDC 135	120 - 135	120	7
MDC 150	135 - 150	120	7
MDC 165	150 - 165	120	7
MDC 175	160 - 175	120	7
MDC 195	180 - 195	120	7.5
MDC 212	197 - 212	120	7.5
MDC 225	210 - 225	120	7.5

Also produced in Nitrile rubber and with grade 1.4401 (316) stainless steel fittings. Please contact us for availability.



DRAIN COUPLINGS APPLICATION SCHEDULE

MDC115 110mm PVCu
100mm Cast Iron (Soil) (SMU/Ensign/SML)
100mm Stainless Steel
100mm Corrugated Plastic
110mm Corrugated Plastic

MDC125 100mm Supersleve
100mm Cast Iron (Drain)
100mm Ductile Iron
100mm Grey Iron
100mm Asbestos Cement
100mm Pitch Fibre
100mm Twin Walled Plastic

MDC135 100mm Supersleve
100mm (4") Salt Glazed Ware
100mm Vitrified Clay
100mm Pitch Fibre
100mm Asbestos Cement

MDC150 125mm Cast Iron (Soil)
125mm Twin Walled Plastic

MDC165 160mm PVCu
150mm Cast Iron (SMU/Ensign/SML)
150mm Stainless Steel
160mm Polyethylene

MDC175 150mm Ultra-Rib
150mm Quantum
150mm Ductile Iron
150mm Grey Iron
150mm Twin Walled Plastic (Wavin/Norflex)
150mm Corrugated Plastic (Wavin/Aquapipe)

MDC195 150mm Supersleve
150mm (6") Salt Glazed Ware
150mm Vitrified Clay
150mm Concrete
150mm Asbestos Cement
150mm Pitch Fibre